

Statement of Basis of the Federal Operating Permit

Nalco Company

Site/Area Name: Nalco Fresno Plant
Physical location: 3130 FM 521 Road
Nearest City: Fresno
County: Fort Bend

Permit Number: O3536
Project Type: Minor Revision

Standard Industrial Classification (SIC) Code: 2869
SIC Name: Industrial Organic Chemicals

This Statement of Basis sets forth the legal and factual basis for the draft changes to the permit conditions resulting from the minor revision project in accordance with 30 TAC §122.201(a)(4). The applicant has submitted an application for a minor permit revision per §§ 122.215-217. This document may include the following information:

- A description of the facility/area process description;
- A description of the revision project;
- A basis for applying permit shields;
- A list of the federal regulatory applicability determinations;
- A table listing the determination of applicable requirements;
- A list of the New Source Review Requirements;
- The rationale for periodic monitoring methods selected;
- The rationale for compliance assurance methods selected;
- A compliance status; and
- A list of available unit attribute forms.

Prepared on: May 5, 2014

Operating Permit Basis of Determination

Description of Revisions

This minor revision to FOP O3536 is for the removal of unit GEN-1 from the permit. This unit is no longer operational. In addition, 30 TAC 115, Storage of VOC, permit shields for low vapor pressure (<1.5 psia) have been removed due to a revision of the rule and appropriate applicabilities have been included in this permit. Terms and Special Conditions have been updated to reflect that there are no 30 TAC 111.111, pre-1972 vents and that all other vents are addressed in the table of applicable requirements. Compliance schedules for units T-7925, T-7947, T-7981, T-4143, PLT1LOAD, PLT2LOAD, PLT3LOAD, PLT4LOAD, TF4LOAD and TF13LOAD have been completed or the unit is out of service and these schedules have been removed from the permit.

Permit Area Process Description

Nalco Company (Nalco) Fresno Plant is a batch operation chemical plant that produces specialty chemicals with the use of reactors, blending vessels, storage tanks and support utilities which currently are authorized by NSR Air Permit No. 4005, and various Permits by Rule (PBRs). The Fresno Plant is divided into separate operating areas, consisting of four plants that share common auxiliary equipment and utilities.

Products are formulated in 14 different reactors and 2 blenders, ranging in sizes from 500 to 6,500 gallons. Bulk, drummed and/or solid raw materials are typically charged into the reactors and blenders. Vent gases are directed to either (1) a control system consisting of a caustic scrubber to remove acid gasses at 99% efficiency followed by the Thermal Oxidizer (EPN TO-1) to control Volatile Organic Compound (VOC) emissions at 99.9%, (2) one of two scrubbers (EPNs S1, S2 and 79S-2A,B,C) with a 99% destruction efficiency, or (3) Flare F-2 (EPN F-2). These raw materials will then be reacted by mixing and heating as necessary. The reactor and blender vents may or may not be opened during this step. A nitrogen purge may be applied during or after the reaction step for certain products (i.e. ethylene oxide and propylene oxide) and will vent to Flare F-1 (EPN F-1). The products will then be cooled as necessary and will either be loaded directly into tank trucks, drums/totes/containers, or transferred to holding tanks, bulk storage or transferred to other reactors acting as holding vessels. Emissions resulting from tank truck loading and packaging operations are controlled by the Thermal Oxidizer for Plants 1, 3 and 4 while emissions from Plant 2 will be routed to a scrubber system (EPN 79S-2A,B,C).

Storage tanks at the Fresno Plant are used to store raw materials, intermediates and finished products associated with the reactors and blenders. The tanks receive raw materials from tank trucks and intermediate and finished products from reactors and blenders. A small portion of the storage tanks have their own individual scrubbers to control emissions while a few others may be routed to Flare F-1 or the Thermal Oxidizer. From these bulk storage tanks, raw materials can be transferred into reactors or blenders while finished products can be loaded out into tank trucks or drums/totes/containers. Emission resulting from these loading and packaging operations will be routed to the Thermal Oxidizer or appropriate scrubber system.

There is also a pilot plant located at the Fresno Plant. The pilot plant consists of five reactors, three pressurized storage tanks and associated tempered oil units for heating and cooling. Product is directly loaded from the reactors into drums. The reactors are routed to either scrubbers PPS-1 or PPS-8.

Nalco is operating Fresno Energy which is an electric energy generating facility that is located nearby the Fresno Plant and is under common control. Fresno Energy includes a Caterpillar G3520C engine that is driving an electric generator to produce 1.47 MW of electrical power. This electrical power is supplied to the power grid and is not used by the Nalco facilities at this site. The engine is fueled with landfill gas.

FOPs at Site

The "application area" consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only

one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: None

Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

| | |
|------------------|-----|
| Major Pollutants | VOC |
|------------------|-----|

Reading State of Texas's Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as “applicable requirements”) that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
 - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
 - Additional Monitoring Requirements
 - New Source Review Authorization Requirements
 - Compliance Requirements
 - Protection of Stratosphere Ozone
 - Permit Location
 - Permit Shield (30 TAC § 122.148)
- Attachments
 - Applicable Requirements Summary
 - Unit Summary
 - Applicable Requirements Summary
 - Additional Monitoring Requirements
 - Permit Shield
 - New Source Review Authorization References
 - Compliance Plan
 - Alternative Requirements
- Appendix A
 - Acronym list

General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding

the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

Attachments

Applicable Requirements Summary. The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the “index number,” detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

Additional Monitoring Requirement. The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References. All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan. A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements. This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

Appendix A

Acronym list. This attachment lists the common acronyms used when discussing the FOPs.

Stationary Vents subject to 30 TAC Chapter 111

All stationary vents subject to 30 TAC Chapter 111 are listed in the permit's Applicable Requirement Summary. The bases for the applicability determinations, for these vents, are listed in the Determination of Applicable Requirements table.

Federal Regulatory Applicability Determinations

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

| Regulatory Program | Applicability (Yes/No) |
|---|-----------------------------------|
| Prevention of Significant Deterioration (PSD) | No |
| Nonattainment New Source Review (NNSR) | No |
| Minor NSR | Yes |
| 40 CFR Part 60 - New Source Performance Standards | Yes |
| 40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs) | No |
| 40 CFR Part 63 - NESHAPs for Source Categories | Yes |
| Title IV (Acid Rain) of the Clean Air Act (CAA) | No |
| Title V (Federal Operating Permits) of the CAA | Yes |
| Title VI (Stratospheric Ozone Protection) of the CAA | Yes |
| CAIR (Clean Air Interstate Rule) | No |

Basis for Applying Permit Shields

An operating permit applicant has the opportunity to specifically request a permit shield to document that specific applicable requirements do not apply to emission units in the permit. A permit shield is a special condition stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements. A permit shield has been requested in the application for specific emission units. For the permit shield requests that have been approved, the basis of determination for regulations that the owner/operator need not comply with are located in the "Permit Shield" attachment of the permit.

Insignificant Activities

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

1. Office activities such as photocopying, blueprint copying, and photographic processes.
2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
4. Outdoor barbecue pits, campfires, and fireplaces.
5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.
6. Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
9. Vehicle exhaust from maintenance or repair shops.
10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
15. Well cellars.
16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
18. Equipment used exclusively for the melting or application of wax.
19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
20. Shell core and shell mold manufacturing machines.

21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
22. Equipment used for inspection of metal products.
23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
25. Battery recharging areas.
26. Brazing, soldering, or welding equipment.

Determination of Applicable Requirements

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html.

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS). These flowcharts can be accessed via the internet at www.tceq.texas.gov/permitting/air/nav/air_supportsys.html. The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column "Changes and Exceptions to RRT." If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word "None" will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled "Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected."

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled “Basis for Applying Permit Shields” specifies which units, if any, have a permit shield.

Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

Determination of Applicable Requirements

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|----------|-------------------------------------|--------------|--|---|
| R-106 | 40 CFR Part 63, Subpart VVVVVV | 63VVVVVV-PV1 | Unit Type = Emission Unit CMPU subject to this 40 CFR Part 63, Subpart VVVVVV | The citations for this rule were determined from the basis of determination provided (i.e. the unit attributes that the applicant should provide when no form exists) and an analysis of the rule text. |
| R106LOAD | 40 CFR Part 63, Subpart VVVVVV | 63VVVVVV-LD1 | Unit Type = Emission Unit CMPU subject to this 40 CFR Part 63, Subpart VVVVVV | The citations for this rule were determined from the basis of determination provided (i.e. the unit attributes that the applicant should provide when no form exists) and an analysis of the rule text. |
| R-106WW | 40 CFR Part 63, Subpart VVVVVV | 63VVVVVV-WW1 | Unit Type = Emission Unit CMPU subject to this 40 CFR Part 63, Subpart VVVVVV | The citations for this rule were determined from the basis of determination provided (i.e. the unit attributes that the applicant should provide when no form exists) and an analysis of the rule text. |
| FWP-1 | 40 CFR Part 63, Subpart ZZZZ | 63ZZZZ-ENG1 | Brake HP = Stationary RICE with a brake hp greater than or equal to 250 hp and less than 300 hp. Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002. Nonindustrial Emergency Engine = Stationary RICE is not defined as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE. Service Type = Emergency use. Stationary RICE Type = Compression ignition engine | |
| FWP-2 | 40 CFR Part 63, Subpart ZZZZ | 63ZZZZ-ENG2 | Brake HP = Stationary RICE with a brake hp greater than or equal to 250 hp and less than 300 hp. Construction/Reconstruction Date = Commenced construction or reconstruction on or after December 19, 2002, but before June 12, 2006. Nonindustrial Emergency Engine = Stationary RICE is not defined as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE. Service Type = Emergency use. Stationary RICE Type = Compression ignition engine | |
| T-4101 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK1 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Product Stored = Other than crude oil, condensate, or VOC | |
| T-4101 | 40 CFR Part 60, Subpart K | 60K-TANK1 | Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|---|---------------------------------|
| T-4103 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK1 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Product Stored = Other than crude oil, condensate, or VOC | |
| T-4103 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK1 | Product Stored = Stored product other than volatile organic liquid or petroleum liquid | |
| T-4105 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-4105 | 40 CFR Part 60, Subpart K | 60K-TANK1 | Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less | |
| T-4106 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-4106 | 40 CFR Part 60, Subpart K | 60K-TANK1 | Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less | |
| T-4107 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-4107 | 40 CFR Part 60, Subpart K | 60K-TANK1 | Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less | |
| T-4118 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK1 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|--|---------------------------------|
| | | | Product Stored = Other than crude oil, condensate, or VOC | |
| T-4118 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK1 | Product Stored = Stored product other than volatile organic liquid or petroleum liquid | |
| T-4119 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-4119 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p> | |
| T-4128 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-4128 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p> | |
| T-4132 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-4132 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK4 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia</p> | |
| T-4134 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|--|---------------------------------|
| | | | <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-4134 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p> | |
| T-4135 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-4135 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p> | |
| T-4137 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK1 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Product Stored = Other than crude oil, condensate, or VOC</p> | |
| T-4137 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK1 | <p>Product Stored = Stored product other than volatile organic liquid or petroleum liquid</p> | |
| T-4142 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK1 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Product Stored = Other than crude oil, condensate, or VOC</p> | |
| T-4142 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK1 | <p>Product Stored = Stored product other than volatile organic liquid or petroleum liquid</p> | |
| T-4143 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-4143 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK4 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|---|---------------------------------|
| | | | (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia | |
| T-4144 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-4144 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-4145 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-4145 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-4146 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-4146 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters) | |
| T-7903 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|---|---------------------------------|
| | | | Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7903 | 40 CFR Part 60, Subpart Ka | 60Ka-TANK1 | Product Stored = Stored product other than a petroleum liquid Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less | |
| T-7904 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7904 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters) | |
| T-7905 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7905 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters) | |
| T-7906 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK1 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Product Stored = Other than crude oil, condensate, or VOC | |
| T-7906 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK1 | Product Stored = Stored product other than volatile organic liquid or petroleum liquid | |
| T-7907 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK1 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Product Stored = Other than crude oil, condensate, or VOC | |
| T-7907 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK1 | Product Stored = Stored product other than volatile organic liquid or petroleum liquid | |
| T-7908 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|---|---------------------------------|
| | | | Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7908 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters) | |
| T-7909 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7909 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7910 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7910 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7911 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7911 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7913 | 30 TAC Chapter | 115-TANK1 | Today's Date = Today's date is March 1, 2013 or later. | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|---|---------------------------------|
| | 115, Storage of VOCs | | Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Product Stored = Other than crude oil, condensate, or VOC | |
| T-7913 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK1 | Product Stored = Stored product other than volatile organic liquid or petroleum liquid | |
| T-7914 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK1 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Product Stored = Other than crude oil, condensate, or VOC | |
| T-7914 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK1 | Product Stored = Stored product other than volatile organic liquid or petroleum liquid | |
| T-7920 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7920 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters) | |
| T-7925 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7925 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7926 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|---|---------------------------------|
| T-7926 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters) | |
| T-7927 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7927 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters) | |
| T-7928 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7928 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters) | |
| T-7929 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7929 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7930 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|---|---------------------------------|
| | | | Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7930 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7934 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7934 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7935 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7935 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7936 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7936 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7938 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|---|---------------------------------|
| | | | Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7938 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7939 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7939 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters) | |
| T-7940 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7940 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7941 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7941 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7942 | 30 TAC Chapter | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|--|---------------------------------|
| | 115, Storage of VOCs | | <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7942 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p> | |
| T-7944 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7944 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p> | |
| T-7947 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7947 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p> | |
| T-7948 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7948 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|--|---------------------------------|
| | | | (75,000 liters) | |
| T-7949 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7949 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p> | |
| T-7950 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7950 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p> | |
| T-7953 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7953 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p> | |
| T-7954 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|---|---------------------------------|
| | | | Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7954 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7955 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7955 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7956 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7956 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7957 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7957 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7958 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|---|---------------------------------|
| | | | Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7958 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7959 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7959 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7960 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7960 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7961 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK3 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7961 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|--|---------------------------------|
| T-7962 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7962 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p> | |
| T-7963 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7963 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p> | |
| T-7964 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7964 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p> | |
| T-7965 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|--|---------------------------------|
| T-7965 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters) | |
| T-7967 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7967 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters) | |
| T-7968 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK1 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Product Stored = Other than crude oil, condensate, or VOC | |
| T-7968 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK1 | Product Stored = Stored product other than volatile organic liquid or petroleum liquid | |
| T-7972 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK4 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons | |
| T-7972 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK4 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia | |
| T-7973 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7974 | 30 TAC Chapter | 115-TANK1 | Today's Date = Today's date is March 1, 2013 or later. | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|--|---------------------------------|
| | 115, Storage of VOCs | | Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Product Stored = Other than crude oil, condensate, or VOC | |
| T-7975 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK1 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Product Stored = Other than crude oil, condensate, or VOC | |
| T-7975 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK2 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters) | |
| T-7976 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK4 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons | |
| T-7976 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK4 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia | |
| T-7977 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7977 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK4 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia | |
| T-7978 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|-------------------------------------|--------------|---|---------------------------------|
| | | | Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7978 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK4 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia | |
| T-7981 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7981 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK4 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia | |
| T-7982 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7982 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK4 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia | |
| T-7983 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons | |
| T-7983 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK4 | Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|----------|--|--------------|--|---------------------------------|
| | | | Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia | |
| T-7984 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7984 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK4 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia</p> | |
| T-7985 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7985 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK4 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia</p> | |
| T-7986 | 30 TAC Chapter 115, Storage of VOCs | 115-TANK2 | <p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> | |
| T-7986 | 40 CFR Part 60, Subpart Kb | 60Kb-TANK3 | <p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p> | |
| PLT1LOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD3 | <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|----------|--|--------------|--|---------------------------------|
| | | | <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p> | |
| PLT1LOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD4 | <p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Loading greater than or equal to 20,000 gallons per day.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p> | |
| PLT2LOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD3 | <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p> | |
| PLT2LOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD5 | <p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Loading greater than or equal to 20,000 gallons per day.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p> | |
| PLT3LOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD3 | <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|----------|--|--------------|--|---------------------------------|
| | | | True Vapor Pressure = True vapor pressure less than 0.5 psia. | |
| PLT3LOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD4 | <p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Loading greater than or equal to 20,000 gallons per day.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p> | |
| PLT4LOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD3 | <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p> | |
| PLT4LOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD4 | <p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Loading greater than or equal to 20,000 gallons per day.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p> | |
| PPLOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD3 | <p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|----------|--|--------------|--|---------------------------------|
| PPLOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD6 | <p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Loading less than 20,000 gallons per day.</p> | |
| TF13LOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD3 | <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p> | |
| TF13LOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD4 | <p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Loading greater than or equal to 20,000 gallons per day.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p> | |
| TF4LOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD3 | <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p> | |
| TF4LOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD4 | <p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|--|--------------|--|---------------------------------|
| | | | <p>automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Loading greater than or equal to 20,000 gallons per day.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p> | |
| UNLOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD1 | <p>Chapter 115 Facitliy Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p> | |
| UNLOAD | 30 TAC Chapter 115, Loading and Unloading of VOC | 115-LOAD2 | <p>Chapter 115 Control Device Type = No control device.</p> <p>Chapter 115 Facitliy Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Loading greater than or equal to 20,000 gallons per day.</p> <p>Control Options = Vapor balance system.</p> | |
| B-1 | 40 CFR Part 60, Subpart Dc | 60DC-BOILER1 | <p>CONSTRUCTION/MODIFICATION DATE = After February 28, 2005.</p> <p>PM MONITORING TYPE = No particulate monitoring.</p> <p>MAXIMUM DESIGN HEAT INPUT CAPACITY = Maximum design heat input capacity is greater than or equal to 10 MMBtu/hr (2.9 MW) but less than or equal to 100 MMBtu (29 MW).</p> <p>SO₂ INLET MONITORING TYPE = No SO₂ monitoring.</p> <p>OTHER SUBPARTS = The facility is not covered under 40 CFR Part 60, Subparts AAAA or KKKK, or under an approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart BBBB.</p> <p>SO₂ OUTLET MONITORING TYPE = No SO₂ monitoring.</p> <p>HEAT INPUT CAPACITY = Heat input capacity is greater than 10 MMBtu/hr (2.9 MW) but less than 30 MMBtu/hr (8.7 MW).</p> <p>TECHNOLOGY TYPE = Other conventional technology.</p> <p>D-SERIES FUEL TYPE = Natural gas.</p> <p>ACF OPTION - SO₂ = Other ACF or no ACF.</p> <p>ACF OPTION - PM = Other ACF or no ACF.</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|---------------------------------------|--------------|--|---------------------------------|
| B-2 | 40 CFR Part 60, Subpart Dc | 60DC-BOILER1 | <p>CONSTRUCTION/MODIFICATION DATE = After February 28, 2005.</p> <p>PM MONITORING TYPE = No particulate monitoring.</p> <p>MAXIMUM DESIGN HEAT INPUT CAPACITY = Maximum design heat input capacity is greater than or equal to 10 MMBtu/hr (2.9 MW) but less than or equal to 100 MMBtu (29 MW).</p> <p>SO₂ INLET MONITORING TYPE = No SO₂ monitoring.</p> <p>OTHER SUBPARTS = The facility is not covered under 40 CFR Part 60, Subparts AAAA or KKKK, or under an approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart BBBB.</p> <p>SO₂ OUTLET MONITORING TYPE = No SO₂ monitoring.</p> <p>HEAT INPUT CAPACITY = Heat input capacity is greater than 10 MMBtu/hr (2.9 MW) but less than 30 MMBtu/hr (8.7 MW).</p> <p>TECHNOLOGY TYPE = Other conventional technology.</p> <p>D-SERIES FUEL TYPE = Natural gas.</p> <p>D-SERIES FUEL TYPE = Other fuel.</p> <p>ACF OPTION - SO₂ = Other ACF or no ACF.</p> <p>ACF OPTION - PM = Other ACF or no ACF.</p> | |
| B-3 | 40 CFR Part 60, Subpart Dc | 60DC-BOILER1 | <p>CONSTRUCTION/MODIFICATION DATE = After February 28, 2005.</p> <p>PM MONITORING TYPE = No particulate monitoring.</p> <p>MAXIMUM DESIGN HEAT INPUT CAPACITY = Maximum design heat input capacity is greater than or equal to 10 MMBtu/hr (2.9 MW) but less than or equal to 100 MMBtu (29 MW).</p> <p>SO₂ INLET MONITORING TYPE = No SO₂ monitoring.</p> <p>OTHER SUBPARTS = The facility is not covered under 40 CFR Part 60, Subparts AAAA or KKKK, or under an approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart BBBB.</p> <p>SO₂ OUTLET MONITORING TYPE = No SO₂ monitoring.</p> <p>HEAT INPUT CAPACITY = Heat input capacity is greater than 10 MMBtu/hr (2.9 MW) but less than 30 MMBtu/hr (8.7 MW).</p> <p>TECHNOLOGY TYPE = Other conventional technology.</p> <p>D-SERIES FUEL TYPE = Natural gas.</p> <p>D-SERIES FUEL TYPE = Other fuel.</p> <p>ACF OPTION - SO₂ = Other ACF or no ACF.</p> <p>ACF OPTION - PM = Other ACF or no ACF.</p> | |
| F-1 | 30 TAC Chapter 111, Visible Emissions | 111-FLARE1 | <p>ACID GASES ONLY [REG I] = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>EMERGENCY/UPSET CONDITIONS ONLY [REG I] = Flare is used under conditions other than emergency or upset conditions.</p> | |
| F-1 | 40 CFR Part 60, Subpart A | 60A-FLARE1 | <p>SUBJECT TO 40 CFR 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>ADHERING TO HEAT CONTENT SPECIFICATIONS = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>FLARE ASSIST TYPE [NSPS A, NESHAP A, AND/OR MACT A] = Non-assisted</p> <p>FLARE EXIT VELOCITY [NSPS A, NESHAP A, AND/OR MACT A] = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|--|--------------|--|---------------------------------|
| F-2 | 30 TAC Chapter 111, Visible Emissions | 111-FLARE1 | ACID GASES ONLY [REG I] = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. EMERGENCY/UPSET CONDITIONS ONLY [REG I] = Flare is used under conditions other than emergency or upset conditions. | |
| F-2 | 40 CFR Part 60, Subpart A | 60A-FLARE1 | SUBJECT TO 40 CFR 60.18 = Flare is subject to 40 CFR § 60.18. ADHERING TO HEAT CONTENT SPECIFICATIONS = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). FLARE ASSIST TYPE [NSPS A, NESHAP A, AND/OR MACT A] = Non-assisted FLARE EXIT VELOCITY [NSPS A, NESHAP A, AND/OR MACT A] = Flare exit velocity is less than 60 ft/s (18.3 m/sec) | |
| FUG | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | R5352-ALL | SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device. Agitators = The fugitive unit contains agitators. Components Utilizing Alternative Work Practice in § 115.358 = No components in the fugitive unit are using the alternative work practice under § 115.358. COMPRESSOR SEALS/VOC SERVICE [REG V] = NO FLANGES = YES OPEN-ENDED VALVES ANDLINES = YES PRESSURE RELIEF VALVES IN GASEOUS VOC SERVICE [REG V] = YES PROCESS DRAINS/VOC SERVICE [REG V] = YES PUMP SEALS IN VOC SERVICE [REG V] = YES RUPTURE DISKS = RELIEF VALVES EQUIPPED WITH A RUPTURE DISK OR VENTING TO A CONTROL DEVICE ARE IN USE. Title 30 TAC § 115.352 Applicable = Site is a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process or a natural gas/gasoline processing operation as defined in 30 TAC 115.10. VALVES OTHER THAN PRESSURE RELIEF OR OPEN-ENDED/VOC SERVICE [REG V] = YES ACR = No agitators are complying with an alternate control requirement. ACR FOR FLANGES = NO ALTERNATE CONTROL REQUIREMENT (ACR)-- VALVES [REG V] = NO ALTERNATE CONTROL REQUIREMENT (ACR)--PRESSURE RELIEF VALVES [REG V] = NO ALTERNATE CONTROL REQUIREMENT (ACR)--PROCESS DRAINS [REG V] = NO ALTERNATE CONTROL REQUIREMENT (ACR)--PUMP SEALS [REG V] = NO INSTRUMENTATION SYSTEMS = FUGITIVE UNIT DOES NOT HAVE INSTRUMENTATION SYSTEMS THAT MEET 40 CFR § 63.169 Less Than 250 Components at Site = Fugitive unit not located at site with less than 250 fugitive components. SAMPLING CONNECTION SYSTEMS = FUGITIVE UNIT DOES NOT HAVE SAMPLING CONNECTION SYSTEMS THAT MEET 40 CFR § 63.169 WEIGHT PERCENT VOC IN PROCESS FLUID [REG V] = COMPONENTS IN THE FUGITIVE UNIT CONTACT PROCESS FLUIDS THAT CONTAIN LESS THAN 10% VOC BY WEIGHT AND PROCESS FLUIDS THAT CONTAIN VOC AT 10%, OR GREATER, BY WEIGHT | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|--|--------------|---|---------------------------------|
| | | | <p>COMPLYING WITH §115.352(1) = YES</p> <p>COMPLYING W/ 30 TAC 115.352(1)--PROCESS DRAINS = YES</p> <p>Complying with § 115.352(1) = Valves are complying with § 115.352(1).</p> <p>Complying With § 115.352(1) = Pressure relief valves are complying with § 115.352(1).</p> <p>Complying With § 115.352(1) = Agitators are complying with § 115.352(1).</p> <p>RECIPROCATING COMPRESSORS OR POSITIVE DISPLACEMENT PUMPS [REG V] = NO RECIPROCATING COMPRESSORS OR POSITIVE DISPLACEMENT PUMPS USED IN NATURAL GAS/GASOLINE PROCESSING OPERATIONS</p> <p>TVP LESS THAN OR EQUAL TO 0.002 PSIA = FUGITIVE UNIT HAS COMPONENTS THAT CONTACT A PROCESS FLUID CONTAINING A PROCESS FLUID CONTAINING VOC HAVING A TRUE VAPOR PRESSURE OF 0.002 PSIA OR LESS</p> <p>TVP LESS THAN OR EQUAL TO 0.044 PSIA AT 68 DEGREES F--PROCESS DRAINS [REG V] = PROCESS FLUID HAS A TRUE VAPOR PRESSURE (TVP) LESS THAN OR EQUAL TO 0.044 PSIA AT 68 DEGREES FAHRENHEIT</p> <p>TVP OF PROCESS FLUID LESS THAN OR EQUAL TO 0.044 PSIA = YES</p> <p>TVP OF PROCESS FLUID VOC <= 0.044 PSI @ 68° = YES</p> <p>TVP of Process Fluid VOC <= 0.044 psia at 68° F = Valves contact a process fluid with a TVP less than or equal to 0.044 psia at 68° F.</p> <p>TVP OR PROCESS FLUID LESS THAN OR EQUAL TO 0.044 PSIA = YES</p> <p>REMAINING SEALS COMPLY WITH 115.352(1)--PUMP SEALS [REG V] = YES</p> <p>TVP GREATER THAN 0.044 PSIA AT 68 DEGREES F--PROCESS DRAINS [REG V] = PROCESS FLUID HAS A TRUE VAPOR PRESSURE (TVP) GREATER THAN 0.044 PSIA AT 68 DEGREES FAHRENHEIT</p> <p>TVP OF PROCESS FLUID > 0.044 PSIA = YES</p> <p>TVP OF PROCESS FLUID VOC > 0.044 PSIA @ 68° F = YES</p> <p>TVP of Process Fluid VOC > 0.044 psia at 68° F = Valves contact a process fluid with a TVP greater than 0.044 psia at 68° F.</p> | |
| PPFUG | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | R5352-ALL | <p>SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.</p> <p>Agitators = The fugitive unit contains agitators.</p> <p>Components Utilizing Alternative Work Practice in § 115.358 = No components in the fugitive unit are using the alternative work practice under § 115.358.</p> <p>COMPRESSOR SEALS/VOC SERVICE [REG V] = NO</p> <p>FLANGES = YES</p> <p>OPEN-ENDED VALVES ANDLINES = YES</p> <p>PRESSURE RELIEF VALVES IN GASEOUS VOC SERVICE [REG V] = YES</p> <p>PROCESS DRAINS/VOC SERVICE [REG V] = YES</p> <p>PUMP SEALS IN VOC SERVICE [REG V] = YES</p> <p>RUPTURE DISKS = RELIEF VALVES EQUIPPED WITH A RUPTURE DISK OR VENTING TO A CONTROL DEVICE ARE IN USE.</p> <p>Title 30 TAC § 115.352 Applicable = Site is a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process or a natural gas/gasoline processing operation as defined in 30 TAC 115.10.</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|------------|--------------|--|---------------------------------|
| | | | <p>VALVES OTHER THAN PRESSURE RELIEF OR OPEN-ENDED/VOC SERVICE [REG V] = YES</p> <p>ACR = No agitators are complying with an alternate control requirement.</p> <p>ACR FOR FLANGES = NO</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR)-- VALVES [REG V] = NO</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR)--PRESSURE RELIEF VALVES [REG V] = NO</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR)--PROCESS DRAINS [REG V] = NO</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR)--PUMP SEALS [REG V] = NO</p> <p>INSTRUMENTATION SYSTEMS = FUGITIVE UNIT DOES NOT HAVE INSTRUMENTATION SYSTEMS THAT MEET 40 CFR § 63.169</p> <p>Less Than 250 Components at Site = Fugitive unit not located at site with less than 250 fugitive components.</p> <p>SAMPLING CONNECTION SYSTEMS = FUGITIVE UNIT DOES NOT HAVE SAMPLING CONNECTION SYSTEMS THAT MEET 40 CFR § 63.169</p> <p>WEIGHT PERCENT VOC IN PROCESS FLUID [REG V] = COMPONENTS IN THE FUGITIVE UNIT CONTACT PROCESS FLUIDS THAT CONTAIN LESS THAN 10% VOC BY WEIGHT AND PROCESS FLUIDS THAT CONTAIN VOC AT 10%, OR GREATER, BY WEIGHT</p> <p>COMPLYING WITH §115.352(1) = YES</p> <p>COMPLYING W/ 30 TAC 115.352(1)--PROCESS DRAINS = YES</p> <p>Complying with § 115.352(1) = Valves are complying with § 115.352(1).</p> <p>Complying With § 115.352(1) = Open-ended valves and lines are complying with § 115.352(1).</p> <p>Complying With § 115.352(1) = Agitators are complying with § 115.352(1).</p> <p>RECIPROCATING COMPRESSORS OR POSITIVE DISPLACEMENT PUMPS [REG V] = NO RECIPROCATING COMPRESSORS OR POSITIVE DISPLACEMENT PUMPS USED IN NATURAL GAS/GASOLINE PROCESSING OPERATIONS</p> <p>TVP LESS THAN OR EQUAL TO 0.002 PSIA = FUGITIVE UNIT HAS COMPONENTS THAT CONTACT A PROCESS FLUID CONTAINING A PROCESS FLUID CONTAINING VOC HAVING A TRUE VAPOR PRESSURE OF 0.002 PSIA OR LESS</p> <p>TVP LESS THAN OR EQUAL TO 0.044 PSIA AT 68 DEGREES F--PROCESS DRAINS [REG V] = PROCESS FLUID HAS A TRUE VAPOR PRESSURE (TVP) LESS THAN OR EQUAL TO 0.044 PSIA AT 68 DEGREES FAHRENHEIT</p> <p>TVP OF PROCESS FLUID LESS THAN OR EQUAL TO 0.044 PSIA = YES</p> <p>TVP OF PROCESS FLUID VOC <= 0.044 PSI @ 68° = YES</p> <p>TVP of Process Fluid VOC <= 0.044 psia at 68° F = Valves contact a process fluid with a TVP less than or equal to 0.044 psia at 68° F.</p> <p>TVP OR PROCESS FLUID LESS THAN OR EQUAL TO 0.044 PSIA = YES</p> <p>REMAINING SEALS COMPLY WITH 115.352(1)--PUMP SEALS [REG V] = YES</p> <p>TVP GREATER THAN 0.044 PSIA AT 68 DEGREES F--PROCESS DRAINS [REG V] = PROCESS FLUID HAS A TRUE VAPOR PRESSURE (TVP) GREATER THAN 0.044 PSIA AT 68 DEGREES FAHRENHEIT</p> <p>TVP OF PROCESS FLUID > 0.044 PSIA = YES</p> <p>TVP OF PROCESS FLUID VOC > 0.044 PSIA @ 68° F = YES</p> <p>TVP of Process Fluid VOC > 0.044 psia at 68° F = Valves contact a process fluid with a TVP greater than 0.044 psia at 68° F.</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|---------------------------------------|--------------|---|---------------------------------|
| R106FUG | 40 CFR Part 60, Subpart VV | 60VV-FUG1 | <p>PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489</p> <p>AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2)</p> <p>40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981</p> <p>40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR</p> | |
| B-1 | 30 TAC Chapter 111, Visible Emissions | 111-VENT1 | <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p> | |
| B-103 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT1 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| B-103 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT6 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor combustor not considered to be a flare.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| B-104 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT1 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|---------------------------------------|--------------|---|---------------------------------|
| | | | distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode. | |
| B-104 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT6 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor combustor not considered to be a flare.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| B-2 | 30 TAC Chapter 111, Visible Emissions | 111-VENT1 | <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p> | |
| B-3 | 30 TAC Chapter 111, Visible Emissions | 111-VENT1 | <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p> | |
| FWP-1 | 30 TAC Chapter 111, Visible Emissions | 111-VENT1 | <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p> | |
| FWP-2 | 30 TAC Chapter 111, Visible Emissions | 111-VENT1 | <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|---------------------------------------|--------------|--|---------------------------------|
| | | | Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute. | |
| HOH-1 | 30 TAC Chapter 111, Visible Emissions | 111-VENT1 | <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p> | |
| HOH-2 | 30 TAC Chapter 111, Visible Emissions | 111-VENT1 | <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p> | |
| HOH-3 | 30 TAC Chapter 111, Visible Emissions | 111-VENT1 | <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p> | |
| HOH-4 | 30 TAC Chapter 111, Visible Emissions | 111-VENT1 | <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p> | |
| R-1 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT3 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|---------------------------------------|--------------|---|---------------------------------|
| | | | <p>combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-100 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT3 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-100 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT6 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor combustor not considered to be a flare.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-101 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT1 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-101 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT2 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Carbon adsorption system.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|---------------------------------------|--------------|---|---------------------------------|
| R-102 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT3 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-102 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT6 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor combustor not considered to be a flare.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-103 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT1 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-103 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT2 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Carbon adsorption system.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-104 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT2 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|---------------------------------------|--------------|---|---------------------------------|
| | | | <p>control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Carbon adsorption system.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-105 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT1 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-105 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT2 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Carbon adsorption system.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-106 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT1 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-106 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT2 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Carbon adsorption system.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|---------------------------------------|--------------|---|---------------------------------|
| R-108 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT1 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-108 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT6 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor combustor not considered to be a flare.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-110 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT1 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-110 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT6 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor combustor not considered to be a flare.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-111 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT6 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|---------------------------------------|--------------|--|---------------------------------|
| | | | Control Device Type = Vapor combustor not considered to be a flare. Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode. | |
| R-112 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT1 | Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Smokeless flare Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode. | |
| R-112 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT6 | Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Vapor combustor not considered to be a flare. Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode. | |
| R-113 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT1 | Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Smokeless flare Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode. | |
| R-113 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT6 | Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Vapor combustor not considered to be a flare. Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode. | |
| R-114 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT6 | Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|---------------------------------------|--------------|---|---------------------------------|
| | | | <p>Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor combustor not considered to be a flare.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-2 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT3 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-4 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT3 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-7 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT3 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| R-8 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT3 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|---------------------------------------|--------------|--|---------------------------------|
| | | | <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10, designed and operated in a batch mode.</p> | |
| T-7901 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT4 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> | |
| T-7902 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT4 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> | |
| T-7931 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT4 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> | |
| T-7932 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT4 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|---------|---------------------------------------|--------------|--|---------------------------------|
| | | | specifically classified under the rule. | |
| T-7951 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT4 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> | |
| T-7952 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT4 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> | |
| T-7969 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT4 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> | |
| T-7970 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT4 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> | |
| T-7979 | 30 TAC Chapter 115, Vent Gas Controls | 115-VENT5 | <p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter</p> | |

| Unit ID | Regulation | Index Number | Basis of Determination* | Changes and Exceptions to DSS** |
|----------|--|--------------|---|---------------------------------|
| | | | <p>B, Division 2.</p> <p>Control Device Type = Carbon adsorption system.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is less than 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p> | |
| TO-1 | 30 TAC Chapter 111, Visible Emissions | 111-VENT1 | <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p> | |
| DEGREASE | 30 TAC Chapter 115, Degreasing Processes | 115-DEGREASE | <p>30 TAC CHAPTER 115 (REG V) SOLVENT DEGREASING MACHINE TYPE = COLD SOLVENT CLEANING MACHINE</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = EXECUTIVE DIRECTOR HAS NOT APPROVED AN ALTERNATE CONTROL REQUIREMENT AS ALLOWED UNDER 30 TAC 115.413.</p> <p>SOLVENT SPRAYED [REG V] = SOLVENT IS NOT SPRAYED</p> <p>SOLVENT VAPOR PRESSURE [REG V] = LESS THAN OR EQUAL TO 0.6 PSIA AS MEASURED AT 100 DEGREES FAHRENHEIT [SOLVENT DEGREASING MACHINE TYPE = 'COLD' OR 'RRC-S']</p> <p>SOLVENT HEATED = SOLVENT NOT HEATED TO A TEMPERATURE GREATER THAN 120 DEGREES FAHRENHEIT</p> <p>PARTS LARGER THAN DRAINAGE [REG V] = SOME CLEANED PART FOR WHICH MACHINE IS AUTHORIZED IS NOT LARGER THAN INTERNAL DRAINAGE FACILITY OF MACHINE.</p> <p>DRAINAGE AREA [REG V] = AREA LESS THAN 16 SQUARE INCHES</p> <p>DISPOSAL IN ENCLOSED CONTAINERS [REG V] = WASTE SOLVENT PROPERLY DISPOSED OF IN ENCLOSED CONTAINERS</p> | |

* - The "unit attributes" or operating conditions that determine what requirements apply

** - Notes changes made to the automated results from the DSS, and a brief explanation why

NSR Versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

| NSR Permit | Federal Operating Permit(FOP) |
|---|--|
| Issued Prior to new Construction or modification of an existing facility | For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation. |
| Authorizes air emissions | Codifies existing applicable requirements, does not authorize new emissions |
| Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented. | Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP. |
| Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations. | One public notice required. Opportunity for public comments. No contested case hearings. |
| Applies to all point source emissions in the state. | Applies to all major sources and some non-major sources identified by the EPA. |
| Applies to facilities: a portion of site or individual emission sources | One or multiple FOPs cover the entire site (consists of multiple facilities) |
| Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis. | Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site. |
| Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources. | Opportunity for EPA review, Affected states review, and a Public petition period for every FOP. |
| Permits have a table listing maximum emission limits for pollutants | Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements. |
| Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin. | Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated. |
| NSR permits are issued independent of FOP requirements. | FOP are independent of NSR permits, but contain a list of all NSR permits incorporated by reference |

New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room, located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. The Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. The following table specifies the permits by rule that apply to the site. All current permits by rule are contained in Chapter 106. Outdated 30 TAC Chapter 106 permits by rule may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106list/index106.html

Outdated Standard Exemption lists may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html

| Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area. | |
|---|------------------------------|
| Authorization No.: 103687 | Issuance Date: 07/18/2012 |
| Authorization No.: 111189 | Issuance Date: 08/08/2013 |
| Authorization No.: 4005 | Issuance Date: 02/06/2012 |
| Permits By Rule (30 TAC Chapter 106) for the Application Area | |
| Number: 106.124 | Version No./Date: 09/04/2000 |
| Number: 106.183 | Version No./Date: 09/04/2000 |
| Number: 106.261 | Version No./Date: 11/01/2003 |
| Number: 106.262 | Version No./Date: 11/01/2003 |
| Number: 106.263 | Version No./Date: 11/01/2001 |
| Number: 106.264 | Version No./Date: 09/04/2000 |
| Number: 106.433 | Version No./Date: 09/04/2000 |
| Number: 106.454 | Version No./Date: 11/01/2001 |
| Number: 106.472 | Version No./Date: 09/04/2000 |
| Number: 106.476 | Version No./Date: 09/04/2000 |
| Number: 106.478 | Version No./Date: 09/04/2000 |

Emission Units and Emission Points

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sand-blasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the “Maximum Allowable Emission Rate Table”, or “MAERT” for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

Monitoring Sufficiency

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit’s compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected

Periodic Monitoring:

The Federal Clean Air Act requires that each federal operating permit include monitoring sufficient to assure compliance with the terms and conditions of the permit. Most of the emission limits and standards applicable to emission units at Title V sources include adequate monitoring to show that the units meet the limits and standards. For those requirements that do not include monitoring, or where the monitoring is not sufficient to assure compliance, the federal operating permit must include such monitoring for the emission units affected. The following emission units are subject to periodic monitoring requirements because the emission units are subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement that does not already require monitoring, or the monitoring for the applicable requirement is not sufficient to assure compliance:

| Unit/Group/Process Information | |
|--|-----------------------------------|
| ID No.: B-1, B-2, B-3 | |
| Control Device ID No.: N/A | Control Device Type: N/A |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 111, Visible Emissions | SOP Index No.: 111-VENT1 |
| Pollutant: OPACITY | Main Standard: § 111.111(a)(1)(B) |
| Monitoring Information | |
| Indicator: Visible Emissions | |
| Minimum Frequency: once per quarter | |
| Averaging Period: n/a | |
| Deviation Limit: Visible emissions exceeding 20% opacity. | |
| <p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p> | |

| Unit/Group/Process Information | |
|--|-----------------------------|
| ID No.: DEGREASE | |
| Control Device ID No.: N/A | Control Device Type: N/A |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 115, Degreasing Processes | SOP Index No.: 115-DEGREASE |
| Pollutant: VOC | Main Standard: § 115.412(1) |
| Monitoring Information | |
| Indicator: Visual Inspection | |
| Minimum Frequency: Monthly | |
| Averaging Period: n/a | |
| Deviation Limit: Any monitoring data that indicates the cold cleaner is not in compliance with the applicable requirements of 115.412(1)(A)-(F) shall be reported as a deviation. | |
| <p>Basis of monitoring:</p> <p>The monitoring option to cover cold cleaner or the open-top vapor cleaner was included in the EPA “Periodic Monitoring Technical Reference Document” (April 1999) to monitor VOC sources. In addition to covering the cleaner records of monthly inspections of equipment is an effective way to ensure that the system is operating in accordance with its design.</p> | |

| Unit/Group/Process Information | |
|--|-----------------------------------|
| ID No.: FWP-1, FWP-2 | |
| Control Device ID No.: N/A | Control Device Type: N/A |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 111, Visible Emissions | SOP Index No.: 111-VENT1 |
| Pollutant: OPACITY | Main Standard: § 111.111(a)(1)(B) |
| Monitoring Information | |
| Indicator: Visible Emissions | |
| Minimum Frequency: once per quarter | |
| Averaging Period: n/a | |
| Deviation Limit: Visible emissions greater than 20% opacity. | |
| <p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p> | |

| Unit/Group/Process Information | |
|--|-----------------------------------|
| ID No.: HOH-1, HOH-2, HOH-3, HOH-4 | |
| Control Device ID No.: N/A | Control Device Type: N/A |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 111, Visible Emissions | SOP Index No.: 111-VENT1 |
| Pollutant: OPACITY | Main Standard: § 111.111(a)(1)(B) |
| Monitoring Information | |
| Indicator: Visible Emissions | |
| Minimum Frequency: once per calendar quarter | |
| Averaging Period: n/a | |
| Deviation Limit: Opacity exceeds 20%. | |
| <p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations. The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p> | |

| Unit/Group/Process Information | |
|---|--------------------------------------|
| ID No.: PLT1LOAD | |
| Control Device ID No.: TO-1 | Control Device Type: Vapor Combustor |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 115, Loading and Unloading of VOC | SOP Index No.: 115-LOAD4 |
| Pollutant: VOC | Main Standard: § 115.212(a)(1) |
| Monitoring Information | |
| Indicator: Combustion Temperature / Exhaust Gas Temperature | |
| Minimum Frequency: Once per week | |
| Averaging Period: n/a* | |
| Deviation Limit: Exhaust gas temperature falls below 1400 degrees F. | |
| <p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p> | |

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

| Unit/Group/Process Information | |
|--|--|
| ID No.: PLT2LOAD | |
| Control Device ID No.: S79-2A,B,C | Control Device Type: Carbon Adsorption System (Non-Regenerative) |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 115, Loading and Unloading of VOC | SOP Index No.: 115-LOAD5 |
| Pollutant: VOC | Main Standard: § 115.212(a)(1) |
| Monitoring Information | |
| Indicator: VOC Concentration | |
| Minimum Frequency: Daily | |
| Averaging Period: N/A | |
| Deviation Limit: First canister not replaced or event not recorded when breakthrough occurs. Also when first canister concentration exceeds 500 ppm. | |
| <p>Basis of monitoring:</p> <p>A common way to monitor a non-regenerative carbon adsorption system is by measuring the outlet VOC concentration with a portable analyzer with procedures such as EPA Test Method 25A or a VOC CEMS. An increase in VOC concentration demonstrates when the carbon canister needs to be replaced. This indicator is consistent with the EPA "CAM Technical Guidance Document" (August 1998) and "Periodic Monitoring Technical Reference Guidance Document" (April 1999). Outlet VOC concentration has been used as an indicator of VOC emissions in many federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, and RRR; and 30 TAC Chapter 115.</p> | |

| Unit/Group/Process Information | |
|---|--------------------------------------|
| ID No.: PLT3LOAD | |
| Control Device ID No.: TO-1 | Control Device Type: Vapor Combustor |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 115, Loading and Unloading of VOC | SOP Index No.: 115-LOAD4 |
| Pollutant: VOC | Main Standard: § 115.212(a)(1) |
| Monitoring Information | |
| Indicator: Combustion Temperature / Exhaust Gas Temperature | |
| Minimum Frequency: Once per week | |
| Averaging Period: n/a* | |
| Deviation Limit: Exhaust gas temperature falls below 1400 degrees F. | |
| <p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p> | |

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

| Unit/Group/Process Information | |
|---|--------------------------------------|
| ID No.: PLT4LOAD | |
| Control Device ID No.: TO-1 | Control Device Type: Vapor Combustor |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 115, Loading and Unloading of VOC | SOP Index No.: 115-LOAD4 |
| Pollutant: VOC | Main Standard: § 115.212(a)(1) |
| Monitoring Information | |
| Indicator: Combustion Temperature / Exhaust Gas Temperature | |
| Minimum Frequency: Once per week | |
| Averaging Period: n/a* | |
| Deviation Limit: Exhaust gas temperature falls below 1400 degrees F. | |
| <p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p> | |

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

| Unit/Group/Process Information | |
|---|--------------------------------|
| ID No.: T-7961 | |
| Control Device ID No.: N/A | Control Device Type: N/A |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 115, Storage of VOCs | SOP Index No.: 115-TANK3 |
| Pollutant: VOC | Main Standard: § 115.112(e)(1) |
| Monitoring Information | |
| Indicator: Structural Integrity of the Pipe | |
| Minimum Frequency: Emptied and degassed | |
| Averaging Period: n/a | |
| Deviation Limit: Deviation occurs if repairs to the fill pipe are not completed prior to refilling the storage vessel. | |
| <p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the “Periodic Monitoring Technical Reference Document” (April 1999) to monitor VOC sources.</p> | |

| Unit/Group/Process Information | |
|---|--------------------------------|
| ID No.: T-7961 | |
| Control Device ID No.: N/A | Control Device Type: N/A |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 115, Storage of VOCs | SOP Index No.: 115-TANK3 |
| Pollutant: VOC | Main Standard: § 115.112(e)(1) |
| Monitoring Information | |
| Indicator: Liquid Level | |
| Minimum Frequency: Once per day | |
| Averaging Period: n/a | |
| Deviation Limit: Deviation occurs when the liquid level falls below the bottom of the open end of the fill pipe. | |
| <p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the “Periodic Monitoring Technical Reference Document” (April 1999) to monitor VOC sources.</p> | |

| Unit/Group/Process Information | |
|---|--------------------------------------|
| ID No.: TF13LOAD | |
| Control Device ID No.: TO-1 | Control Device Type: Vapor Combustor |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 115, Loading and Unloading of VOC | SOP Index No.: 115-LOAD4 |
| Pollutant: VOC | Main Standard: § 115.212(a)(1) |
| Monitoring Information | |
| Indicator: Combustion Temperature / Exhaust Gas Temperature | |
| Minimum Frequency: Once per week | |
| Averaging Period: n/a* | |
| Deviation Limit: Exhaust gas temperature falls below 1400 degrees F. | |
| <p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p> | |

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

| Unit/Group/Process Information | |
|---|--------------------------------------|
| ID No.: TF4LOAD | |
| Control Device ID No.: TO-1 | Control Device Type: Vapor Combustor |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 115, Loading and Unloading of VOC | SOP Index No.: 115-LOAD4 |
| Pollutant: VOC | Main Standard: § 115.212(a)(1) |
| Monitoring Information | |
| Indicator: Combustion Temperature / Exhaust Gas Temperature | |
| Minimum Frequency: Once per week | |
| Averaging Period: n/a* | |
| Deviation Limit: Exhaust gas temperature falls below 1400 degrees F. | |
| <p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p> | |

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

| Unit/Group/Process Information | |
|--|-----------------------------------|
| ID No.: TO-1 | |
| Control Device ID No.: N/A | Control Device Type: N/A |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 111, Visible Emissions | SOP Index No.: 111-VENT1 |
| Pollutant: OPACITY | Main Standard: § 111.111(a)(1)(B) |
| Monitoring Information | |
| Indicator: Visible Emissions | |
| Minimum Frequency: once per quarter | |
| Averaging Period: n/a | |
| Deviation Limit: Visible emissions exceeding 20% opacity. | |
| <p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p> | |

Available Unit Attribute Forms

OP-UA1 - Miscellaneous and Generic Unit Attributes
OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes
OP-UA3 - Storage Tank/Vessel Attributes
OP-UA4 - Loading/Unloading Operations Attributes
OP-UA5 - Process Heater/Furnace Attributes
OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes
OP-UA7 - Flare Attributes
OP-UA8 - Coal Preparation Plant Attributes
OP-UA9 - Nonmetallic Mineral Process Plant Attributes
OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes
OP-UA11 - Stationary Turbine Attributes
OP-UA12 - Fugitive Emission Unit Attributes
OP-UA13 - Industrial Process Cooling Tower Attributes
OP-UA14 - Water Separator Attributes
OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes
OP-UA16 - Solvent Degreasing Machine Attributes
OP-UA17 - Distillation Unit Attributes
OP-UA18 - Surface Coating Operations Attributes
OP-UA19 - Wastewater Unit Attributes
OP-UA20 - Asphalt Operations Attributes
OP-UA21 - Grain Elevator Attributes
OP-UA22 - Printing Attributes
OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes
OP-UA25 - Synthetic Fiber Production Attributes
OP-UA26 - Electroplating and Anodizing Unit Attributes
OP-UA27 - Nitric Acid Manufacturing Attributes
OP-UA28 - Polymer Manufacturing Attributes
OP-UA29 - Glass Manufacturing Unit Attributes
OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semichemical Pulp Mill Attributes
OP-UA31 - Lead Smelting Attributes
OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes
OP-UA33 - Metallic Mineral Processing Plant Attributes
OP-UA34 - Pharmaceutical Manufacturing
OP-UA35 - Incinerator Attributes
OP-UA36 - Steel Plant Unit Attributes
OP-UA37 - Basic Oxygen Process Furnace Unit Attributes
OP-UA38 - Lead-Acid Battery Manufacturing Plant Attributes
OP-UA39 - Sterilization Source Attributes
OP-UA40 - Ferroalloy Production Facility Attributes
OP-UA41 - Dry Cleaning Facility Attributes
OP-UA42 - Phosphate Fertilizer Manufacturing Attributes
OP-UA43 - Sulfuric Acid Production Attributes
OP-UA44 - Municipal Solid Waste Landfill/Waste Disposal Site Attributes
OP-UA45 - Surface Impoundment Attributes
OP-UA46 - Epoxy Resins and Non-Nylon Polyamides Production Attributes
OP-UA47 - Ship Building and Ship Repair Unit Attributes
OP-UA48 - Air Oxidation Unit Process Attributes
OP-UA49 - Vacuum-Producing System Attributes
OP-UA50 - Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes

OP-UA51 - Dryer/Kiln/Oven Attributes
OP-UA52 - Closed Vent Systems and Control Devices
OP-UA53 - Beryllium Processing Attributes
OP-UA54 - Mercury Chlor-Alkali Cell Attributes
OP-UA55 - Transfer System Attributes
OP-UA56 - Vinyl Chloride Process Attributes
OP-UA57 - Cleaning/Depainting Operation Attributes
OP-UA58 - Treatment Process Attributes
OP-UA59 - Coke By-Product Recovery Plant Attributes
OP-UA60 - Chemical Manufacturing Process Unit Attributes
OP-UA61 - Pulp, Paper, or Paperboard Producing Process Attributes
OP-UA62 - Glycol Dehydration Unit Attributes
OP-UA63 - Vegetable Oil Production Attributes